

Application Areas

Recommended for use on all interior new bare or previously varnished or stained wood surfaces.

Surface Preparation

If applying to previously finished wood, sand in order to remove old coating before applying new finish. If sanding entire surface is not desired, only sand areas of distress that can cause flaking in order to blend edges. Apply the product directly to the surface or the sealer coatings.

Lead Warning! Scraping, sanding or removal of a lead coating may release lead dust. **Lead is toxic. Before you start,** find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log onto www.epa.gov/lead.

Application

1. Test the finish on a sample piece of wood. Soft or porous woods such as pine, alder, birch, fir, cedar, or redwood may absorb a finish unevenly. Also, some woods contain tannins and other extractives that will bleed through to the surface and affect appearance.
2. Stir prior to use. Apply thin, even coats with a brush and/or spray-gun (conventional or low-pressure system), taking care to prevent the finish from puddling. Overlap brush/spray gun strokes and always maintain a wet edge.
3. Apply with a brush and/or spray-gun (conventional or low-pressure system) without thinning. Excessive thinning may result in reduced product performance.
4. Sand lightly between each coat with very fine sandpaper (220 grit) and remove dust with water-dampened cloth. Never use steel wool or a tack cloth.
5. Recoat in 2 hours under normal conditions. High humidity or low temperature may lengthen the dry time.
6. Apply 3 coats for optimum performance.
7. For best results, apply in temperatures between 65°F--80°F with a 40%-60% relative humidity. Do not apply in direct sunlight.

Precautions

Vermont Natural Coatings' PolyWhey products have low VOC levels, but should still be used with adequate ventilation. Provide adequate fresh air entry. If ventilation is inadequate, use an organic vapor/particulate respirator approved by NIOSH/MSHA for spray/mist vapors. When sanding a dried coating film use a dust/mist respirator approved by NIOSH/MSHA.

This product does not contain formaldehyde or other toxic ingredients that would require protective clothing. However, for those who are chemically sensitive or who will use this product over a long period of time, we recommend wearing protective gloves and safety glasses with side shields.

Keep out of reach of children. Do not take internally. Avoid contact with eyes and prolonged contact with skin.

This product is not flammable, but all polymer film once it is applied can burn and containers could explode if exposed to extreme heat or fire. Avoid breathing fumes of burning dry coating because carbon dioxide/monoxide may be released. Extinguish with foam, CO₂, dry chemicals, or water fog.

Drying/Curing

Under normal conditions and with good ventilation, wood treated will be dry and ready for use in 2-3 hours. Allow one week for full product cure.

Cleanup

Wipe excess finish out of the lip of container with a clean cloth prior to sealing to avoid gluing lid closed. Reseal original container immediately after use to reduce skinning or contamination of the product. Brushes and other equipment can be cleaned with warm, soapy water.

Disposal

Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Dispose of container and any remaining liquid product in accordance with local, state, and federal regulations. Contact local solid waste officials for handling requirements.

General guidelines:

- Do not rinse empty cans out before disposal. Open can and allow to air dry.
- Empty, dry containers may be recycled. If recycling is unavailable, dispose of empty containers in trash.
- Do not put containers that contain liquid product in the trash. Contact local officials for local recycling and disposal guidance.

Storage

1. Store in a dry, ventilated, and cool place and keep from freezing.
2. Keep lid closed tightly and container in upright position, away from fire, open flame, or high-temperature areas.
3. Shelf life is 12 months from date of manufacture under normal temperature conditions and if the container is resealed correctly to prohibit contamination.
4. Reseal original container immediately after use to reduce skinning or contamination of the product.

Guarantee

We guarantee your satisfaction with our products. If proper pre-application and application techniques have been followed and you are not satisfied with the results, please contact us. We welcome your feedback and will provide you with replacement product, credit, or a cash refund.

Limited Liability

Liability, whether expressed or implied, is limited to replacement of product or refund of purchase price and cannot include liability for labor costs or consequential damages. It is the user's responsibility to determine the suitability and safety of the product for any particular application. This limited warranty may not be modified or extended by manufacturer's representatives, distributors, or dealers of Vermont Natural Coating products.

For questions or comments, please call 1-802-472-8700, Mon- Fri 9:00 AM to 5:00 PM (EST). For more information on Vermont Natural Coatings or our wood finishing ideas, check out our web site at www.vermontnaturalcoatings.com.

VERMONT
NATURAL
COATINGS™

P.O. Box 512
180 Junction Rd.
Hardwick, Vermont 05843