

# PolyWhey<sup>®</sup>

## 3500

### Wood Floor Finish

## The new standard in wood floor finishes

- A single-component water based floor finish for commercial and heavy residential use.
- Safe, durable, and easy to apply, it surpasses the competition in both abrasion and mar resistance and will outperform other waterborne coatings in the toughest commercial settings.
- Unlike other wood floor finishes, it meets the highest professional application and environmental standards without compromising performance and durability.



# PolyWhey<sup>®</sup> 3500 Professional Wood Floor Finish

## FEATURES & BENEFITS

- Single-Component formulation means no wasted finish
- Superior durability and ability to withstand discoloration in high-traffic areas
- Excellent flow and leveling results in easy application and beautiful finished floors
- At 95 g/L, PolyWhey 3500 complies with all US and Canadian VOC regulations
- Fast drying time offers the ability to apply up to 3 coats in one day
- Neutral odor allows for coating in occupied areas without disrupting residents/visitors
- With no carcinogens or isocyanates, PolyWhey 2500 has no flash point and will not contribute toward cancer or fire risks

## AVAILABILITY

UPC-A	DESCRIPTION	QTY/PK	PKS/CS	CASE WT. (LBS.)	CASE DIMENSIONS
<b>Norton/Vermont Natural Coatings Floor Finish</b>					
076607 68150 8	Matte - 1 Gallon	4	1	38	11" x 14.5" x 10"
076607 68151 5	Matte - 5 Gallon	1	1	45	15" x 12" x 12"
076607 68133 1	Satin - 1 Gallon	4	1	38	11" x 14.5" x 10"
076607 68134 8	Satin - 5 Gallon	1	1	45	15" x 12" x 12"
076607 68135 5	Semi-Gloss - 1 Gallon	4	1	38	11" x 14.5" x 10"
076607 68136 2	Semi-Gloss - 5 Gallon	1	1	45	15" x 12" x 12"
<b>Norton/Vermont Natural Coatings Floor Sealer</b>					
076607 68130 0	Sealer - 1 Gallon	4	1	38	11" x 14.5" x 10"
076607 68131 7	Sealer - 5 Gallon	1	1	45	15" x 12" x 12"

## REPORT CARD

		PolyWhey 3500 Satin	Bona Traffic <sup>®</sup> Satin w/crosslinker	Basic StreetShoe <sup>®</sup> 275 Satin w/crosslinker	Pallmann X-98 Satin w/crosslinker
<b>PERFORMANCE</b>	<b>Test</b>	<b>ASTM</b>			
	<b>Taber performance:</b> How localized abrasion wears through a coating	ASTM D 4060/ AC-04-09 rev 1	< 1% loss	< 1% loss	< 1% loss
	<b>Black heel mar:</b> How a coating resists discoloration and damage from daily foot traffic	ASTM 5170/ AC-04-18 rev 2	5 out of 5 (5 is highest)	2	3
	<b>Scuff mar:</b> How weight and grit will reduce sheen and film thickness	ASTM 5170/ AC-04-18 rev 2	5 test average: 9.9/10	4	3
<b>SAFETY AND VALUE</b>	<b>Characteristic</b>				
	VOC in grams per liter		95	210	250
	Whey Technology		Yes	No	No
	Contains mutagen NMP		No	No	No
	Contains OSHA regulated isocyanate in crosslinker		No	Yes	No
	Renewable content		Yes	No	No
	No waste single component		Yes	No	No
	Coverage		600-700	350-400	550-700
Cost per square foot		\$.18	\$.28	\$.14	

\*All testing done by 3rd party

### What Contractors are saying about PolyWhey 3500:

In this market, everyone is looking for a “bang” for their buck and with this product I'm able to provide the customer with an amazing product and I'm able to get more coverage per gallon at a lesser price per sq/ft than competitive product.

– Nu-Floor Hardwood Flooring, Toms River, NJ

PolyWhey 3000 Sealer also available!

[www.facebook.com/NortonDIYContractor](http://www.facebook.com/NortonDIYContractor) | [www.youtube.com/NortonDIYContractor](http://www.youtube.com/NortonDIYContractor) | [www.nortonfloorsanding.com](http://www.nortonfloorsanding.com)

#### USA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 551-4415  
Phone: 1 (254) 918-2306  
Fax: 1 (254) 918-2309

#### CANADA CUSTOMER SERVICE:

Toll Free Phone: 1 (800) 263-6565  
Toll Free Fax: 1 (800) 561-9490

#### TECHNICAL SUPPORT:

VERMONT NATURAL COATINGS, INC.  
Toll Free Phone: 1 (888) 639-9439  
Phone: 1 (802) 472-8700  
Fax: 1 (802) 472-8755  
info@vermontnaturalcoatings.com  
[www.vermontnaturalcoatings.com](http://www.vermontnaturalcoatings.com)

#### FORM #8545

© Saint-Gobain September 2014.  
Norton is a registered trademark of Saint-Gobain Abrasives.  
PolyWhey<sup>®</sup> is a registered trademark of Vermont Natural Coatings, Inc.  
All other trademarks are the property of their respective owners.

