

VERMONT NATURAL COATINGS® BÖHME

SWISS QUALITY  SINCE 1866



Böhme has been manufacturing stains and coatings in Switzerland since 1866. Now these natural hybrid-oil stains and finishes are made in the USA and available throughout North America through a partnership with Vermont Natural Coatings. The Böhme line, for both interior and exterior applications, applies, penetrates and looks like a traditional oil. These coatings clean up with soap and water, are easy to use and maintain, and are still < 30g/L VOC.

EXTERIOR TRIM STAIN BoMol

Clear

Pure
Natural

Western
Red Cedar

Butternut

Walnut

TWO INNOVATIVE COMPANIES with a Shared Mission



Vermont Natural Coatings' revolutionary technology and 150 years of Böhme experience combine to deliver the safest, highest quality coatings in the world.
SWISS QUALITY MADE IN THE USA.

BoMol is a natural oil / waterborne hybrid stain that protects wood from damaging UV rays and delivers a paint-like surface build. It is formulated for exterior wood trim, doors windows and siding. It can be used on new or pre-stained wood.



Vermont Natural Coatings, Inc
www.VermontNaturalCoatings.com
info@VermontNaturalCoatings.com
(802) 472-8700 Find us on 

VERMONT NATURAL COATINGS®

BÖHME

BOMOL

Through an innovative manufacturing process, Böhme harnesses the strengths of natural oil finishes into a safe, premium waterbased product.

RECOMMENDED USES:

Ideal for exterior wood trim, doors, windows and siding. Can be used on new or pre-stained wood.



Available in Quart, Gallon, and Five Gallon

- Protects wood from UV rays
- Long lasting and high performance
- Paint-like surface build with the penetration of a stain
- Excellent flow and uniform color
- Low maintenance
- Custom colors available upon request
- Clean up with soap and water



• Premium Exterior Stains & Finishes •

PREPARATION & APPLICATION



SURFACE PREPARATION: Remove old finishes and/or remove all loose and defective material. If coating unfinished softwood, it is recommended to use **Suncare 900** as pre-treatment. For all other unfinished woods, pre-treat with **Böhme Hydro-Oil Primer**. Be certain surface is thoroughly cleaned and dried.

APPLICATION:

Apply when no rain is expected for 24 hours. For pressure treated wood allow 3-6 months before application. Not suitable for subterranean or submerged wood.



1) Stir well prior to use.



2) Test stain on a sample piece of wood or less visible area of surface to be finished.



3) Apply with brush, paint pad, roller or spray.



4) Two coats are recommended on all sides of wood.



5) Apply evenly with the grain and always maintain a wet edge. If rolling, follow with brush or paint pad.

6) For best results apply in temperatures between 45°-80°F and relative humidity of 40%-60%. **Do not apply when rain is expected within 24 hours.**



7) Product will be ready for second coat after 24 hours. **One gallon will cover approximately 250-350 sq. ft.** depending on porosity of wood.

TECHNICAL DATA

<i>Color in Container</i>	Refer to label
<i>Clarity (Dry)</i>	Semi-Solid
<i>Chemical Resistance</i>	No visual defects
<i>VOC</i>	Coating: 30g/L (wet)
<i>Flash Point</i>	None
<i>Freeze/Thaw Stability</i>	Do not freeze
<i>Pot Life</i>	12 months from date of manufacture
<i>Dry Time</i>	24 hours
<i>Clean Up</i>	Soap and water
<i>Odor</i>	Neutral
<i>Maximum Cure</i>	One week
<i>Coverage</i>	250 -350 sq. ft. per gallon

Vermont Natural Coatings, Inc
info@VermontNaturalCoatings.com
(802) 472-8700 Find us on

For project ideas and testimonials visit: www.vermontnaturalcoatings.com