

VERMONT NATURAL COATINGS®

PolyWhey®

Professional Wood Finish Made Green.™

PolyWhey®, a revolutionary, patented technology delivers durable, safe and easy to use paints, stains and finishes that have established the highest performance and environmental standards. PolyWhey uses whey protein- a byproduct of cheese making- as the transformative ingredient.

A Better Whey



Superior Durability

Premium durability with patented PolyWhey formula



Red List Free

No chemicals causing cancer, birth defects, or reproductive harm



No California Prop 65 Ingredients

Protects ground and drinking water from toxic chemicals



Qualifies for LEED Credits

Complies with VOC laws in all 50 states and Canada



Green Innovation

Derived from recycled and renewable whey protein



PolyWhey® Heirloom Fine Finish

Vermont Natural Coatings PolyWhey® Heirloom Fine Finish is our safest, most durable furniture finish with the look and feel of traditional hand rubbed finishes. Heirloom Fine Finish is ideal as a top-coat on furniture, cabinets, doors and trim to enhance the beauty of the wood.



Durable • Safe • Easy to use

Vermont Natural Coatings, Inc

www.VermontNaturalCoatings.com

info@VermontNaturalCoatings.com

(802) 472-8700 Find us on

VERMONT NATURAL COATINGS®

PolyWhey®

HEIRLOOM FINE FINISH

By using whey protein as a co-binder, PolyWhey leverages a renewable resource to deliver the safest and most durable paints, stains and finishes on the market.

RECOMMENDED USES:

Ideal as a top-coat on furniture, cabinets, doors and trim to enhance the beauty and durability of the wood.



Available in Quarts

- High durability
- Neutral odor
- Non-flammable
- Easy to apply
- Soap and water cleanup
- Transparent and non-yellowing
- Ultra-Low VOC (under 30g/L)
- Available in Satin



Durable • Safe • Easy to use

PREPARATION & APPLICATION

SURFACE PREPARATION: Surfaces must be clean, dry and free of any grease, glue or other contaminants.

APPLICATION:



1) Stir well prior to use.



2) Be sure wood surface is thoroughly clean and dry.



3) Using a lint free cloth, paint pad, or quality synthetic or foam brush, apply thin, even coats in the direction of the grain.



4) Finish will be dry and ready to recoat in two hours. After the second coat, sand lightly using 400 grit sandpaper.



5) Four to six coats recommended.

6) One quart will cover approximately 125-150 sq/ft.

EASY CLEANUP: Brushes and other equipment can be cleaned with warm, soapy water.

TECHNICAL DATA

<i>Color in Container</i>	Milky White
<i>Clarity (Dry)</i>	Crystal Clear
<i>Solids Content</i>	15%
<i>Chemical Resistance</i>	No visual defects
<i>VOC</i>	Coating: ≤30g/L (wet)
<i>Flash Point</i>	None
<i>Sheen</i>	Satin: 25 units (±) @ 60°
<i>Freeze/Thaw Stability</i>	Do not freeze
<i>Pot Life</i>	12 months from date of manufacture
<i>Dry Time</i>	30-40 minutes to touch
<i>Clean Up</i>	Soap and hot water
<i>Odor</i>	Neutral
<i>Maximum Cure</i>	One week
<i>Coverage</i>	150-175 sq. ft. per quart

Vermont Natural Coatings, Inc
info@VermontNaturalCoatings.com
(802) 472-8700 Find us on

For project ideas and testimonials visit: www.vermontnaturalcoatings.com